



RAWLPLUG CODE	APPLICATION	EMBEDMENT DEPTH	HEAD DRIVE	ANCHOR DRILL DIA.	ETA /CE	AVAILABLE LENGTHS	MATERIAL
KI-10 + KWL090PP 	INSULATION BOARDS TO MASONRY PERIMETER FIXING	25MM HAMMERFIX WITH PIN	HAMMERFIX	10.0MM	 ETA A-E 	70 - 220MM (40 - 190MM INS. THICK)	POLYPROPYLENE & GLASS REINFORCED PIN
MBA-SS & MKC-SS 	INSULATION BOARDS TO MASONRY CENTRE FIXING	30MM (ITB) & 50MM	HAMMERFIX	8.0MM	MFPA FIRE REPORT	90 - 300MM (60 - 270MM INS. THICK)	CARBON STEEL ZINC PLATED & STAINLESS STEEL
WB-48 OR WX-48T + KC/KCX & KWL-090PP 	INSULATION BOARDS TO SHEATHING BOARDS PERIMETER FIXING	N/A	8.0MM HEX (WB) OR TX25 (WX-48T)	N/A	 ETA • ETA-09/0346 	50 - 300MM (30 - 415MM INS. THICK)	CARBON STEEL SCREWS ZINC FLAKE POLYPROPYLENE WASHERS & TUBES
OCS & ONS BI-METAL SELF-DRILL SCREWS & MKC-SS-70-8 WASHERS 	INSULATION BOARDS TO SHEATHING BOARDS & STEEL STUDDING CENTRE FIXING	N/A	8.0MM HEX	N/A	 ETA • ETA-09/0346 	70 - 230MM	CARBON STEEL ZINC PLATED & BI-METAL STAINLESS STEEL
WBT-61 CONCRETE SCREW & R-DB-Z WASHER OR POK WASHERS 	SOFFIT SLAB BOARDS TO CONCRETE SOFFITS	25MM	TX25	5.0MM		50 - 300MM	CARBON STEEL SCREWS ZINC FLAKE
MBA & MBA-SS 	SOFFIT SLAB BOARDS TO CONCRETE SOFFITS	50MM	HAMMERFIX	8.0MM	MFPA FIRE REPORT	90 - 300MM (40 - 250MM INS. THICK) & COVER CAPS	CARBON STEEL ZINC PLATED & STAINLESS STEEL

TEK SCREWS FOR LIGHT STEEL FRAMING SYSTEMS



RAWLPLUG CODE	APPLICATION	THREAD DIA.	HEAD DRIVE	STEEL CAP.	ETA /CE	AVAILABLE LENGTHS	MATERIAL
<p>OC & OCS-48</p>	STEEL FRAME TO STEEL FRAME	4.8MM	8.0MM	0.75 - 3.0MM	<p>ETA-13/0203</p>	16 - 55MM	CARBON STEEL PLATED & BI-METAL STAINLESS
<p>OC & OCS-55</p>	STEEL FRAME TO STEEL FRAME	5.5MM	8.0MM	1.0 - 6.0MM	<p>ETA-13/0203</p>	22 - 120MM	CARBON STEEL PLATED & BI-METAL STAINLESS
<p>ON & ONS-55</p>	STEEL FRAME TO HOT ROLLED STEEL	5.5MM	8.0MM	4.0 - 12.0MM	<p>ETA-13/0203</p>	ON-55 (32 & 38MM) ONS-55 (40MM)	CARBON STEEL PLATED & BI-METAL STAINLESS
<p>ONP-55 LARGE FLANGE CLADDING SCREW</p>	STEEL FRAME TO HOT ROLLED STEEL	5.5MM	8.0MM	4.0 - 12.0MM	<p>ETA-13/0203</p>	ON-55 (32 & 38MM) ONS-55 (40MM)	CARBON STEEL PLATED
RAWLPLUG CODE	APPLICATION	EMBEDMENT DEPTH	HEAD DRIVE	ANCHOR DRILL DIA.	ETA /CE	AVAILABLE LENGTHS	MATERIAL
<p>WCS FLG CONCRETE SCREWS</p>	STEEL FRAME TO CONCRETE	30MM	8.0MM	5.0MM	<p>ETA-09/0346</p>	28 - 100MM	CARBON STEEL ZINC FLAKE
<p>R-LX-P CONCRETE SCREWS</p>	STEEL FRAME TO CONCRETE	30MM	TX30	6.0MM	<p>ETA 17/0783</p>	40MM	CARBON STEEL ZINC PLATED
<p>R-LX-P CONCRETE SCREWS</p>	STEEL FRAME TO CONCRETE	43MM OR 55MM	10MM	6.0MM	<p>ETA 17/0783</p>	50 - 150MM	CARBON STEEL ZINC FLAKE